

CERTIFICATE OF THOROUGH EXAMINATION SHACKLE



Issued By:



Date of Issue: 03-05-2025

Certificate No.: **JO-10649**

This equipment certificate complies with the requirements of Emirates International Accreditation Centre for inspection bodies working in the field of Lifting Equipment and Lifting Accessories (EIAC-RQ-IB-002), reference standard BS EN 13889:2003+A1:2008 and Manufacturer's Specification.

Owner Name: NA
Office Address: P.O.Box 51445,
Dubai,
United Arab Emirates
Equipment Location: NA

INSPECTION DETAILS					
Date of Inspection:	03-05-2025		Expiry Date:	03-05-2025	
Inspection Type:	THOROUGH				
Previous Inspection Report:	bb	Last Proof Load Test:		03-05-2025	
Test Method	CSI-06	Calibrated Test Equipment:		gy	
		Client Test Equipment:		gg	
EQUIPMENT INFORMATION					
EQUIPMENT ID & SERIAL NO.:	EQUIPMENT DESCRIPTION	QTY	WORKING LOAD LIMIT	TEST LOAD APPLIED	TYPE OF TEST & RESULT
fa	Manufacturer: fa Shackle Diameter: 54 Grade: fa	2	54	54	fs
The owner shall perform the next inspection no later than 2 Months From the date of issue.					

This is to certify that the above item/s described in this certificate was tested and particulars are correct.

CSSC has inventoried, inspected, verified and tested above mentioned equipment in accordance with the reference standards cited herein and consistent with CSSC policies and procedure. We certify this above mentioned equipment is **SAFE TO USE**, condition prevails at the time of this inspection, safe to use further with qualified operator. That the owner or his designated agent or contractor, hereafter owner, continues to perform maintenance in accordance with the original equipment manufacturer's preventive maintenance guideline and procedures and makes no unauthorized changes to the equipment's controls and mechanisms. CSSC makes no claims regarding the condition or safety of the equipment after we have completed this inspection and departed the property. CSSC disclaims any warranty of any kind either expressed or implied including without limitation warranties of merchantability or fitness for a particular purpose. This certificate becomes invalid in the event of any repair or alterations are done, in which case it must be retested.

All the information obtained /gathered during the inspection shall be preserved as confidential.

This inspection has been carried out as per local order no. : 2/2010;

This inspection certificate / report shall not be reproduced except in full without the approval of Claymore and the Client.

Inspected By: Wazeem Ibrahim

Name & Signature of Inspector

CERTIFICATE OF THOROUGH EXAMINATION SHACKLE

Date of Issue: 03-05-2025

CertificateNo.: **JO-10649**

ThinkSafe! ThinkSafe! ThinkSafe! ThinkSafe! ThinkSafe! ThinkSafe! ThinkSafe! ThinkSafe! ThinkSafe! ThinkSafe!

EXAMINATION REPORT						
EQUIPMENT PARTS		S	NS	NA	SE	REMARKS
Document verification						
1.	Manufacturer's Declaration of Conformity (if New)	☐	☐	☒	☐	
2.	Previous Third Party Inspection (If Used)	☐	☐	☒	☐	
Component						
3.	Check shackle for clear & legible marked with a unique identification mark, manufacturer's name or symbol, working load limit (WLL)	☐	☐	☒	☐	
4.	Grade of material of shackle constructed from is identified, i.e grade 6.	☐	☐	☒	☐	
5.	Shackle body and pin must be of the same grade	☐	☐	☒	☐	
6.	Check for wear not more than 8% reduction in material diameter on either the pin or the body	☐	☐	☒	☐	
7.	Inside width at pin:					
	0.5t up to and including 2t : $\pm 2.5\text{mm}$	☐	☐	☒	☐	
	3.25t up to and including 9.5t : $\pm 3\text{mm}$	☐	☐	☒	☐	
	12t up to and including 25t : $\pm 4\text{mm}$	☐	☐	☒	☐	
8.	Max diameter of unthreaded hole in shackle 1.1 x D or D+1.5mm (where D is the actual pin diameter), (whichever is the greater) and holes must be align	☐	☐	☒	☐	
9.	Bearing points (shackle and pin)	☐	☐	☒	☐	
Bow Diameter (Tolerance)						
10.	Bow Diameter:					
	0.5 up to and including 2t : $+ 1.5\text{mm} / - 1\text{mm}$	☐	☐	☒	☐	
	3.25 up to and including 12t : $\pm 2.5\text{mm}$	☐	☐	☒	☐	
	13.25 up to and including 25t : $\pm 3\text{mm}$	☐	☐	☒	☐	
Shackle Pin (Tolerance)						
11.	Pin Diameter:					
	0.5 up to and including 2t : $\pm 1\text{mm}$	☐	☐	☒	☐	
	3.25 up to and including 25t : $\pm 2\text{mm}$	☐	☐	☒	☐	
12.	<u>Thread:</u> Visible thread after tightening in between jaws not more than 1.5 thread pitch (for screw pin) or there shall be no thread visible between the jaws of the shackle (for bolt & nut pin)	☐	☐	☒	☐	
13.	Pin must be correctly screwed into the shackle eye	☐	☐	☒	☐	
14.	Collar diameter or width across the flats of the nut shall be at least 1.2 D or D+3mm (whichever is greater)	☐	☐	☒	☐	
15.	<u>All shackle pins:</u> 13mm diameter and above, shall be legibly and indelibly marked with the relevant grade number traceability code and manufacturer's symbol in a manner which will not impair the mechanical properties of the pin.	☐	☐	☒	☐	
	Pins below 13mm diameter shall be marked with at least either the grade number or the traceability code.	☐	☐	☒	☐	
16.	Verify availability & condition of split pin if applicable	☐	☐	☒	☐	
17.	Check and verify applicable local color coding	☐	☐	☒	☐	
S-Satisfactory, NS-Not Satisfactory, NA-Not Applicable, SE-Serviceable • Finding • Critical Finding						
Finding: bh		Critical Finding: gg			Other Remarks: f	
Target Date of Closure:		Target Date of Closure:				

CERTIFICATE OF THOROUGH EXAMINATION SHACKLE



Issued By:



Date of Issue: 03-05-2025

CertificateNo.: **JO-10649**

Think Safe! Think Safe! Think Safe! Think Safe! Think Safe! Think Safe! Think Safe! Think Safe! Think Safe! Think Safe!

PHOTOS OF INSPECTED SHACKLES